Dräger

Dräger Alcotest[®] 6820 Alcohol Screening Device

Dräger Alcotest[®] 6820 is the logical successor to the successful Alcotest[®] 6810. The compact hand-held measuring instrument Alcotest[®] is quickly ready for use and is adaptable to international guidelines. With an even more sturdy enclosure and the proven Dräger sensor, Alcotest[®] 6820 is a reliable partner for breath alcohol analyses.



Interface for charging the NiMH battery pack or as a data interface

Benefits

High-quality workmanship

A professional breath alcohol testing device must be able to withstand some abuse. The Alcotest 6820 new design and quality workmanship make this unit ideal for use in demanding conditions. Thanks to its durable material it is highly resistant to rough weather conditions such as cold or moisture, and it satisfies protection class IP 54.

High user comfort

Testing intoxicated people requires a high degree of concentration. This is where the true value of an easy to operate device comes into play. All measurement functions are controlled with a single button. Easily understandable full-text messages on a large, backlit display guide you safely through the alcohol test. An LED display and acoustic signals support the visual display and report the completion of a test measurement. Two menu buttons are used for navigation and the collection of statistical data.

Proven quality

Alcotest 6820 is also equipped with the proven electrochemical Dräger sensor. This sensor is characterised by very short response times coupled with precision and durability. Test results are always reliable regardless whether the temperature is -5 °C or +50 °C. Even with a high alcohol content, the sensor provides fast accurate results. And this is true for both active as well as passive measurements.

Practical design

Alcotest 6820 offers a balanced, ergonomic design. Its compact form makes it especially easy to hold and operate with only one hand. The mouthpiece of the Alcotest 6820 unit is easily snapped into the holder even when it's dark thanks to its intuitive shape - regardless whether you are right-handed or left-handed or whether testing traffic moving on the right or left side of the road. The display is always in clear view. After use, the mouthpiece is just as easily and hygienically removed again.

"Slide'n'Click" mouthpiece

The patented Dräger mouthpieces prevent any manipulation attempts. The optional return valve simultaneously ensures maximum hygiene. Alcotest 6820 uses the same reliable mouthpieces such as Alcotest models 6510 and 6810.

Data processing and documentation

The expanded memory capacity of Alcotest 6820 is able to record up to 5000 test results. An optical interface enables wireless transmission of data to the Dräger mobile printer directly on site. Data is transferable to the PC via USB connection and the same connection can be used to configure the device.

Benefits

Optional accessories

A wide strap supports safe and comfortable use of the Alcotest 6820 testing device. The strap can be attached to your belt or around the wrist and secured with either buckles or Velcro. Reflectors make it easier to locate the device in the dark.

Accessories

D-9486-2014



Accessories



Leather pouch

Leather pouch in black or yellow for belt fastening

Printer

Dräger Mobile Printer prints breath alcohol and drug test measurement results without using a dedicated power supply. Operates on 4 AA batteries.

Related Products



Dräger Alcotest[®] 5510

As entry level model of the successful Dräger Alcotest[®] 6510 the Dräger Alcotest[®] 5510 offers professional users precise and quick breath alcohol analysis in a user-friendly and compact form. Thanks to its wide range of possible configurations, the handheld instrument can be easily adapted to meet different international regulations and guidelines.

Related Products



Dräger Alcotest[®] 7510

The Dräger Alcotest[®] 7510 is a compact and robust handheld breath alcohol measuring instrument, especially designed for advanced screening applications. Ideal for use by police as well as in commerce and industry as an alcohol screening device, it can also be used for evidential testing purposes, subject to relevant local and market sector approvals.

Dräger DrugTest[®] 5000

No pipetting, no drips, no timing: Collecting an oral fluid sample is quick and easy with the Dräger DrugTest[®] 5000. The collected sample can then be analysed immediately for accurate results on the spot.



D-54720-2012

Dräger DCD 5000

Simple, fast and secure detection of intoxicants and drugs: The Dräger DCD 5000 does not only enable an easy collection of saliva, you can also store the samples and send them to the laboratory for analysis – without the sample being falsified along the way.



Dräger Interlock® 7000

The Dräger Interlock[®] 7000 is an alcohol ignition interlock device. After a breath alcohol measurement it prevents an drunk driver from starting the vehicle. The Interlock[®] 7000 is very quickly ready for use. Additionally, the device can be equipped with a camera and/or a GPRS module, according to the specific customer requirements.

Technical Data

Test method	Electrochemical Dräger sensor for 1/4" technology; alcohol- specific
Test range	0 to 2.5 mg/L; display indication when exceeding test range
Sampling	Standard: automatic sampling when minimum volume is reached
	Passive sampling or manual triggering of sampling possible
Ready for use	Approx. 2 s after powering up
Test result display	Approx. 3 s (with 0 mg/l), 10 s (at 0.5 mg/l, room temperature)
Operating temperature	-5 to +50 °C; -4 to +122 °F
Display	Graphic LCD display with background illumination; 41 mm x 24 mm (128 x 64 pixels)
LED	3 colours to indicate messages or alerts
Acoustic alarms	Different signal tones indicate various messages and alerts
Memory	Space for saving the last 5000 tests with test number, date and time
Power supply	Two AA batteries or NiMH batteries, battery indicator on the
	display.
	Around 1500 breath tests can be conducted with one set of
	batteries.
	Charging rechargeable NiMH batteries is possible in device
Calibration	Wet gas or dry gas calibration
Dimensions (H x W x D), weight	147 mm x 65 mm x 39 mm, approx. 260g
Device configuration	Device settings configurable directly via device menu (PIN required).
	No additional PC software required
Vibration and impact	Meets EN 60068-2-6, EN 60068-2-27, EN 60068-2-64,
	MIL-STD 810F
CE marking	Directive 89/336/EEC (electromagnetic compatibility)
Data interfaces	USB to PC; optical interface for printer control
Standard	Meets EN 15964
Protection type	IP 54

Ordering Information

83 22 660
68 10 690
68 10 825
68 10 830
68 11 055
68 11 060
68 11 065
83 16 991
83 20 252
83 19 715

Notes

Notes

compatible | Subject to modifications | © 2015 Drägerwerk AG & Co. KGaA entally c 90 94 088 | 15-04-2 | Communications & Sales Marketing | PP | LE | Printed in Germany | Chlorine-free -

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

Manufacturer:

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany

REGION EUROPE CENTRAL

AND EUROPE NORTH Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION EUROPE SOUTH

Dräger Safety France SAS 25, rue Georges Besse 92182 Antony Cedex Tel +33 1 46 11 56 00 Fax +33 1 40 96 97 20 europe.south@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Safety Asia Pte Ltd 25 International Business Park #04-20/21 German Centre Singapore 609916 Tel +65 6308 9400 Fax +65 6308 9401 asia.pacific@draeger.com

REGION CENTRAL

AND SOUTH AMERICA Dräger Panama S. de R.L. Complejo Business Park, V tower, 10th floor Panama City Tel +507 377 9100 Fax +507 377 9130 contactcsa@draeger.com

Locate your Regional Sales Representative at: www.draeger.com/contact

