

Workman Self-retracting Lanyard offers lightweight, durable thermoplastic housing for years of dependable service. RFID-enabled product simplifies product tracking and inspection. Integral, ergonomic carrying handle eases transport and installation; 136 kg working capacity increases versatility. Available in 9 and 15-m length and galvanized or stainless steel lifeline.



Features & Benefits

| FEATURES | BENEFITS |
|---|---|
| Integrated carrying handle | Makes carrying and installing easy |
| Lightweight | 9m unit weights just 5.4 kg |
| RFID-enabled | Simplifies product tracking and inspection |
| Swivel snaphook | Greatly limits twisting of cable |
| Load indicator integrated into snaphook | Visual indicator shows the unit has been involved in a fall |

Product Specifications

| Material | |
|---------------------------|--|
| Cover | PC + thermoplastic |
| Frame | Zinc coated steel |
| Hub | Aluminium |
| Cable | 5mm, galvanized steel or stainless steel cable |
| Termination | Swivel steel snaphook, 21 mm |
| Technical Specifications | |
| Maximum arrest force | 6 kN |
| Working temperature range | -40°C to 60°C |
| Maximum capacity | 136 kg |
| Minimum breaking strength | 15 kN |
| Weight | 5,4 kg (9m) / 7,8 kg (15m) |
| Approvals | |
| EN 360:2002 | |

Ordering Information

| Part No. | Description |
|----------|--|
| 10120722 | MSA Workman SRL, 9 m, galvanised cable |
| 10120723 | MSA Workman SRL, 9 m, stainless-steel cable |
| 10121776 | MSA Workman SRL, 15 m, galvanised cable |
| 10121777 | MSA Workman SRL, 15 m, stainless-steel cable |