

Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Fall arrest lanyards



ABSORBICA-I VARIO

Adjustable single lanyard with a compact, integrated energy absorber designed for protection on a horizontal lifeline (rope or cable) or on an elevated platform. This lanyard features the VARIO adjustment system, allowing the lanyard length to be adjusted in order to reduce the potential fall height. ABSORBICA-I VARIO is certified to European and Russian standards.



VARIO adjustment system allows the lanyard length to be adjusted from 150 to 100 cm in order to reduce the potential fall height.

Short Description Adjustable single lanyard with integrated energy absorber

- Selling Points**
- Designed for protection on a horizontal lifeline (rope or cable) or on an elevated platform
 - VARIO adjustment system allows the lanyard length to be adjusted from 150 to 100 cm in order to reduce the potential fall height
 - Absorbs energy in case of a fall:
 - tearing of the energy absorber webbing limits the impact force on the user
 - works with users who weigh between 50 and 130 kg
 - progressive tearing reduces the deceleration on lightweight users
 - Minimal bulk: compact energy absorber facilitates handling
 - Abrasion resistance:
 - durable zippered fabric pouch protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
 - lanyard and pouch reduce the risk of cuts and potential severing over edges
 - Two options for installation on the harness, depending on use:
 - frequent connection/disconnection: with a carabiner held in correct position by the STRING (included with the lanyard)
 - semi-permanent connection: with a RING OPEN, whose circular shape ensures optimal positioning
 - Two connector options for the end of the lanyard: a locking carabiner, or MGO OPEN connector with large gate opening

-
- Specification**
- Material(s): polyester, nylon, aluminum
 - Certification(s): CE EN 355, CE EN 354, EAC
-

Specifications by reference

Reference(s)	L64IAR 150
Maximum length	150 cm
Minimum length	100 cm
Connector	without connector
Maximum authorized length (with connectors)	200 cm
Maximum length of torn lanyard after fall	320 cm
Maximum clearance (for fall factor 2)	620 cm
Weight	280 g
Made in	FR
Guarantee	3 years
Packing	1
Case quantity	10
EAN	3342540103962

Accessory(ies) MGO OPEN 60

Related product(s) VOLT®
OK
Am'D
RING OPEN