

Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Rope access lanyards



PROGRESS

The PROGRESS progression lanyard allows continuous connection during rope ascents. The connectors are held in the correct position for ease of clipping.



The plastic sheath holds the connector in place. It also protects the ends of the lanyard from abrasion.

Short Description Progression lanyard

Selling Points

- Double lanyard allows continuous connection during rope ascents:
 - long arm for attaching an ASCENSION handled rope clamp
 - short arm for clipping in when passing intermediate anchors
- Ends equipped with a plastic sheath that holds the connector in place and protects against abrasion
- Dynamic rope lanyard to limit the impact transmitted to the user in case of a short fall (1)
- Used with two VERTIGO TWIST-LOCK auto-locking carabiners

(1) Progression lanyards do not have energy absorbers. They thus should only be used if the fall factor is less than 1 (used below the ASCENSION handled rope clamp or anchor point).

Specification

- Weight: 150g
 - Certification(s): CE EN 354, EAC
 - Short arm length: 30 cm
 - Long arm length: 65 cm
-

Specifications by reference

Reference(s)	L44A
Made in	DE
Guarantee	3 years
Packing	1
Case quantity	25
EAN	3342540103443

Related product(s)	ASCENSION VERTIGO TWIST-LOCK AVAO® BOD European version AVAO® BOD international version AVAO® BOD FAST European version AVAO® BOD FAST international version RING OPEN
---------------------------	--